





.

Indoor advertising totem - Full HD 55" LCD -Non touch - Android


Ref. DLS55-V2-2+16

Indoor advertising totem 55" Non-touch. It features a simple and elegant design, made with durable materials and quality finishes. Reproduce images in high definition, ensuring great visibility and visual impact. Its setup is very simple as it features an Android operating system. Content can be displayed via USB or online using software. This versatile digital signage solution will attract customers in shopping malls, stores, or restaurants, capturing their attention and increasing sales. Product subject to special shipping conditions in the mainland and Balearic Islands: +100 (+VAT shipping costs - No additional discounts or coupons accepted



Product data

Speakers2 X SWAudioMP3, M4A, WAV, WMACertsCE, ROHSColors16.7 millionConnectivityBluetooth 4.2, Ethernet, HDMI INPUT, RJ45 (Ethernet), USB, Wi-Fi (2.4 GH2), Wi-Fi (802.11b/g/n)Dimensions (mm) LxWxH1900 x 790 x 440Frequency (Hz)1.9 GHzFrequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsGPUMali-G31 / Four coresInagesJPG, BMP, PNGIPIP20Brightness350 cd/m²RAM2GBTemperature range-20°F-70°FRentingYearsOperating systemAndroid PInotahNeNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseMPEGA, WMX, WBCPUT972 - Cuatro núcleos	Storage	16GB
CertsCE, ROHSColors16.7 millionConnectivityBluetooth 4.2, Ethernet, HDMI INPUT, RJ45 (Ethernet), USB, Wi-Fi (2.4 GH2), Wi-Fi (802.11b/g/n)Dimensions (mm) LxWxH1900 x 790 x 460Frequency (Hz)1.9GHzFrequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsGPUMali-G31 / Four coresImagesJPG, BMP, PNGIPIP20Brightness350 cd/m²Inches55 inchesRAM2GBTemperature range-20°F-70°FRentingYesResolution1920 x 1080Operating systemAndroid 9TouchNoNominal Voltage (V)220 - 240 V ACResponse time& msDisplay TypeLCDOutdoor UseNpEG4, WWV, VPBVideoMPEG4, WWV, VPB	Speakers	2 X 5W
Colors16.7 millionConnectivityBluetooth 4.2, Ethernet, HDMI INPUT, RJ45 (Ethernet), USB, Wi-Fi (2.4 GHz), Wi-Fi (802.11b/g/n)Dimensions (mm) LxWxH1900 x 790 x 460Frequency (Hz)1.9GHzFrequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsGPUMali-G31 / Four coresImagesJPG, BMP, PNGIPIP20Brightness350 cd/m²Inches55 inchesRAM2GBTemperature range-20°F-70°FRentingYesResolution1920 x 1080Operating systemAndroid 9TouchNoNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WtW, VPR	Audio	MP3, M4A, WAV, WMA
ConnectivityBluetooth 4.2, Ethernet, HDMI INPUT, RJ45 (Ethernet), USB, Wi-Fi (2.4 GHz), Wi-Fi (802.11b/g/n)Dimensions (mm) LxWxH1900 x 790 x 460Frequency (Hz)1.9GHzFrequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsGPUMali-G31 / Four coresImagesJPG, BMP, PNGIPIP20Brightness350 cd/m²Inches55 inchesRAM2GBTemperature range-20°F-70°FRentingYesResolution1920 x 1080Operating systemAndroid 9TouchNoNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VP8	Certs	CE, ROHS
Dimensions (mm) LxWxH1900 x 790 x 460Frequency (Hz)1.9GHzFrequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsGPUMali-G31 / Four coresImagesJPG, BMP, PNGIPIP20Brightness350 cd/m²Inches55 inchesRAM2GBTemperature range-20°F-70°FRentingYesResolution1920 x 1080Operating systemAndroid 9TouchNoNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseMPEG4, WMV, VPB	Colors	16.7 million
Frequency (Hz)1.9GHzFrequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsGPUMali-G31 / Four coresImagesJPG, BMP, PNGIPIP20Brightness350 cd/m²Inches55 inchesRAM2GBTemperature range-20°F-70°FRentingYesResolution1920 x 1080Operating systemAndroid 9TouchNoNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VP8	ConnectivityBluetooth 4.2, Ethernet, HDMI INPUT, RJ45 (Ethernet), USB, Wi-Fi (2.4 GHz), Wi-Fi (802.11b/g/n)	
Frequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsGPUMali-G31 / Four coresImagesJPG, BMP, PNGIPIP20Brightness350 cd/m²Inches55 inchesRAM2GBTemperature range-20°F-70°FRentingYesResolution1920 x 1080Operating systemAndroid 9TouchNoNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VP8	Dimensions (mm) LxWxH	1900 x 790 x 460
GuaranteeAccording to legal warranty: 3 yearsGPUMali-G31 / Four coresImagesJPG, BMP, PNGIPIP20Brightness350 cd/m²Inches55 inchesRAM2GBTemperature range-20°F~70°FRentingYesResolution1920 x 1080Operating systemAndroid 9TouchNoNomianl Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VPB	Frequency (Hz)	1.9GHz
GPUMali-G31 / Four coresImagesJPG, BMP, PNGIPIP20Brightness350 cd/m²Inches55 inchesRAM2GBTemperature range-20°F-70°FRentingYesResolution1920 x 1080Operating systemAndroid 9TouchNoNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VPB	Frequency of Use	Intensive
ImagesJPG, BMP, PNGIPIP20Brightness350 cd/m²Inches55 inchesRAM2GBTemperature range-20°F-70°FRentingYesResolution1920 x 1080Operating systemAndroid 9TouchNoNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VP8	Guarantee	According to legal warranty: 3 years
IPIP20Brightness350 cd/m²Inches350 cd/m²Inches55 inchesRAM2GBTemperature range-20°F~70°FRentingYesResolution1920 x 1080Operating systemAndroid 9TouchNoNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VP8	GPU	Mali-G31 / Four cores
Brightness350 cd/m²Inches350 cd/m²Inches55 inchesRAM2GBTemperature range-20°F~70°FRentingYesResolution1920 x 1080Operating systemAndroid 9TouchNoNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VP8	Images	JPG, BMP, PNG
Inches55 inchesRAM2GBTemperature range-20°F~70°FRentingYesResolution1920 x 1080Operating systemAndroid 9TouchNoNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VP8	IP	IP20
RAM2GBTemperature range-20°F~70°FRentingYesResolution1920 x 1080Operating systemAndroid 9TouchNoNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VP8	Brightness	350 cd/m²
Temperature range-20°F~70°FRentingYesResolution1920 x 1080Operating systemAndroid 9TouchNoNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VP8	Inches	55 inches
RentingYesResolution1920 x 1080Operating systemAndroid 9TouchNoNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VP8	RAM	2GB
Resolution1920 x 1080Operating systemAndroid 9TouchNoNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VP8	Temperature range	-20°F~70°F
Operating systemAndroid 9TouchNoNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VP8	Renting	Yes
TouchNoNominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VP8	Resolution	1920 × 1080
Nominal Voltage (V)220 - 240 V ACResponse time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VP8	Operating system	Android 9
Response time8 msDisplay TypeLCDOutdoor UseNoVideoMPEG4, WMV, VP8	Touch	No
Display Type LCD Outdoor Use No Video MPEG4, WMV, VP8	Nominal Voltage (V)	220 - 240 V AC
Outdoor Use No Video MPEG4, WMV, VP8	Response time	8 ms
Video MPEG4, WMV, VP8	Display Type	LCD
	Outdoor Use	No
CPU T972 - Cuatro núcleos	Video	MPEG4, WMV, VP8
	CPU	T972 - Cuatro núcleos





Product variants

Reference

Attributes



DLS55-V2-2+16